

SMD Crystal Resonators / MHz Band Crystal Resonators DSX321G



 Automotive applications such as Bluetooth, wireless LAN, GPS/GNSS,RKE (Remote Keyless Entry), safety controls and multimedia devices (AEC-Q200 Compliant)

Standard Specification

Item Type	DSX321G						
Frequency Range	7.9 to 9MHz	9 to 9.8MHz	9.8 to 11MHz	11 to 12MHz	12 to 20MHz	20 to 27MHz	27 to 64MHz
Overtone Order	Fundamental						
Load Capacitance	8pF, 10pF, 12pF						
Drive Level	10μW (200μW max.)						
Frequency Tolerance	±20×10 ⁻⁶ (at 25°C)						
Series Resistance	400Ω max.	300Ω max.	150Ω max.	100Ω max.	80Ω max.	60Ω max.	50Ω max.
Frequency Characteristics over Temperature	±30×10 ^{−6} / −30 to +85℃ (Ref. to 25℃)						
Storage Temperature Range	−40 to +85℃						
Packing Unit	3000pcs./reel (\$\$\phi180\$)						

Industrial equipment

Consult our sales representative for other specifications.

DSX321G (under 12MHz)

[mm] DSX321G (over 12MHz)

[mm]

