

TUNING FORK QUARTZ CRYSTAL UNITS A Hosonic



3.2*1.5 32.768KHz Crystal • ETST Series



The SMD type quarta crystal provides ultimate in size, performance, and economic trade-offs. So it is used as a clock source in communication equipment, measuring instrument, microprocessor and other time management application.

FEATURES

- Miniature Package
- Low resistance
- 32.768KHz Frequency
- **Tight Tolerance**
- Size option


Electrical Specifications

Item	Type	ETST
Frequency Range	F0	32.768KHz
Load Capacitance	CL	12.5pF(7.0pF, 9.0pF Option)
Frequency Tolerance	△F/ F0	±20ppm(At 25°C)
Equivalent Series Resistance	ESR	70KΩ Max.
Temperature Cofficient	K	-0.034 ± 0.006 ppm* $(△°ℂ)^2$
Turnover Temperature	T ₀	25±5℃
Operating Temperature Range	Topr	-40~+85°C
Storage Temperature Range	Tstg	-55~+125℃
Shunt Capacitance	C0	2.0pF Max.
Insulator Resistance	IR	500MΩ min. (At 100VDC)
Drive Level	DL	1μW Max.
Aging	Fa	±5ppm max. (At 25°C ,First year)
Packing Unit		3000pcs/reel


^{**}Please contact us for inquiries regarding other Specifications

Mechanical Dimensions(mm)





Recommended Solder Pattern



TAIWAN:

HOSONIC ELECTRONIC CO., LTD. 23-1 LANE 84. CHUN YING ST. SHULIN CHEN. TAIPEI 23804. TAIWAN WEB SITE:http://www.hosonic.com



CHINA:

HANGZHOU HOSONIC ELECTRONIC CO., LTD. NO.242 LIANGBO ROAD. LIANGZHU TOWN. YUHANG DISTRICT, HANGZHOU, ZHEJIANG, CHINA WEB SITE:http://www.hosonic.com

1: 86-571-88778189

: 86-571-88778857 : hosonic.sales@hosonic.com